




ILLUMINATOR DATA - ID

DLW2-60-070-1-R-24V

Lighting Dimension




Mechanical Information	
Casing Material	Aluminium
Storage Temperature Range	Temp 0-45°C, Humidity 20-85%
Weight	190g
Length / Outer Diameter	76.2 X 76.2 mm
Width / Inner Diameter	40 X 40 mm
Thickness	45 mm



ILLUMINATOR DATA - ID

DLW2-60-070-1-R-24V

Optical Information				
Part Number		DLW2-60-070-1-R-24V		
LED Color		RED		
Wavelength	(nm)	620		
Intensity ($\pm 15\%$)	(Lux)	4110	4150	3980
Working Distance	(mm)	12	17	22
Illumination (number of row)		1		
Illumination Active Area				
Active Length / Outer Dia.	(mm)	76.2 X 76.2		
Active Width / Inner Dia.		40 X 40		
Emission angle	(deg.)	60		
Eye Safety Class (IEC62471)		EXEMPT		
Electrical Information				
Lighting Supply Voltage (constant voltage mode)		24V \pm 2%		
Continuous Current	(mA)	120		
Power Consumption	(W)	2.88		
Lighting casing temperature, after 60 minutes	Operating °C	43.9		
Strobe Mode Specification				
Pulse Operation		YES		
Max. Lighting Supply Voltage (Constant voltage power supply)	(V)	Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle Recommended at 36VDC		
Pulse Current, (Max. 10msec) (Constant current power supply)	(mA)	360		
Max. Trigger Pulse Duration	(msec)	10		
Duty Cycle		0-10%		
Additional Information				
Additional Cooling Method		Attached to machine part for better heat dissipation		
Intensity Controller Selection		ANG, ST, SD and SDA series		
CE Conformity		YES		
RoHS Compliance		YES		
Connection				
Connector Type (Default):		JST SMR-03V		
Cable Length out from lighting :	(mm)	500		
Pin Configuration :		Pin	Signal	Cable Color
		1	LED +	RED
		2	N.C.	---
		3	LED -	WHITE
				
Application				
Illumination Type		Diffuser Illumination		
Application Use		Character recognition on shining surface, lead inspection		