




# ILLUMINATOR DATA-ID

**LSW-45-070-3-G-24V**

## Lighting Dimension



SECTION A-A  
SCALE 1 : 1.5


ROHS COMPLIANT CE

| Mechanical Information    |                                |
|---------------------------|--------------------------------|
| Casing Material           | Aluminium                      |
| Storage Temperature Range | Temp 0 - 45°C, Humidity 20-85% |
| Weight                    | 120 g                          |
| Length / Outer Diameter   | 70 mm                          |
| Width / Inner Diameter    | 35 mm                          |
| Thickness / Height        | 21 mm                          |



# ILLUMINATOR DATA-ID

## LSW-45-070-3-G-24V

| Optical Information   |        |  |        |             |
|---|--------|--|--------|-------------|
| Part Number   |        | LSW-45-070-3-G-24V   |        |             |
| LED Color   |        | GREEN  |        |             |
| Wavelength  | (nm)   | 525  |        |             |
| Intensity (±15%)  | (Lux)  | 127200   | 126800 | 113800      |
| Working Distance  | (mm)   | 13   | 18     | 23          |
| Illumination (number of row)                                    |        | 3  |        |             |
| Illumination Active Area  |        |  |        |             |
| Active Length / Outer Diameter                                  | (mm)   | 62.5   |        |             |
| Active Width / Inner Diameter                                   | (mm)   | 40.5   |        |             |
| Emission angle  | (deg.) | 45   |        |             |
| Eye Safety Class ( IEC62471 )                                   |        | EXEMPT   |        |             |
| Electrical Information  |        |  |        |             |
| Lighting Supply Voltage<br>(constant voltage mode)              |        | 24V ± 2%   |        |             |
| Continuous Current  | (mA)   | 240  |        |             |
| Power Consumption   | (W)    | 5.76   |        |             |
| Lighting casing temperature,<br>Operating after 60 minutes      | °C     | 63.6   |        |             |
| Strobe Mode Specification                                       |        |  |        |             |
| Pulse Operation   |        | YES  |        |             |
| Max. Lighting Supply Voltage<br>(Constant voltage power supply) | (V)    | Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle, Recommended at 36VDC                    |        |             |
| Pulse Current, (Max. 10msec)<br>(Constant current power supply) | (mA)   | 720  |        |             |
| Max. Trigger Pulse Duration                                     | (msec) | 10   |        |             |
| Duty Cycle  |        | 0-10%  |        |             |
| Additional Information  |        |  |        |             |
| Additional Cooling Method                                       |        | Attached to machine part for better heat dissipation                                 |        |             |
| Intensity Controller Selection                                  |        | ANG, ST, SD and SDA Series   |        |             |
| CE Conformity   |        | YES  |        |             |
| RoHS Compliance   |        | YES  |        |             |
| Connection  |        |  |        |             |
| Connector Type (Default):                                       |        | JST SMR-03V  |        |             |
| Cable Length out from lighting :                                | (mm)   | 500  |        |             |
| Pin Configuration :   |        | Pin  | Signal | Cable Color |
|   |        | 1  | LED +  | RED         |
|   |        | 2  | N.C.   | ---         |
|   |        | 3  | LED -  | WHITE       |
|   |        |  |        |             |
| Application   |        |  |        |             |
| Illumination Type   |        | Direct Illumination  |        |             |
| Application Use   |        | Substrate inspection, label inspection, flat surface, fiducially recognition.        |        |             |