

BHS3 SERIES - High Intensity Back Light




BHS3 series LED are arranged in a dense array and shine into a diffuser. The even light shines from the diffuser provides area illumination.

Application: lead frame inspection, shape recognition, size measurement.

BHL3 SERIES - High Intensity Back Light

BHL3 series LED are arranged in a dense array and shine into a diffuser. The even light shines from the diffuser provides area illumination.

Application: lead frame inspection, shape recognition, size measurement.

**Technical Specification:**

- Color Red, Green, Blue and White
- 24V DC Input Power
- Continuous and Strobe Applications
- Compact Size
- Lighting Cable 500mm

Customize Lighting:

- Customize Sizes, Mounting requirements
- Color and Voltage Available
- Consult Technical Sales for More Information

Model	Dimensions (MM)							Color	Voltage / Watt	Current
	A	B	C	D	E	F	G			
BHS3-00-020-X-X	52	44	28	22	24	10	15	● ○	24V / 0,72W	30mA
BHS3-00-050-X-X	78	70	54	52	54	40	15	● ○	24V / 1,20W	50mA
BHS3-00-080-X-X	108	100	84	82	84	70	15	● ○	24V / 2,40W	100mA
BHS3-00-100-X-X	128	120	104	102	104	90	15	● ○	24V / 3,60W	150mA
								● ○	24V / 6,00W	250mA
								● ○	24V / 4,80W	200mA
								● ○	24V / 9,12W	380mA
								● ○	24V / 6,84W	285mA

Model	Dimensions (MM)							Color	Voltage / Watt	Current
	A	B	C	D	E	F	G			
BHL3-00-050-X-X	78	70	54	52	54	40	23	● ○	24V / 2,40W	100mA
BHL3-00-080-X-X	108	100	84	82	84	70	23	● ○	24V / 3,60W	150mA
BHL3-00-100-X-X	128	120	104	102	104	90	23	● ○	24V / 6,00W	250mA
								● ○	24V / 4,80W	200mA
								● ○	24V / 9,12W	380mA
								● ○	24V / 6,84W	285mA

Remarks : The current of BHS3-00-020 is changed.