




# ILLUMINATOR DATA

**CAS2-00-010-X-W-24V**

## Lighting Dimension




ROHS COMPLIANT CE

Mechanical Information	
Casing Material	Aluminium
Storage Temperature Range	Temp 0-45°C, Humidity 20-85%
Weight	120g
Length	77.4mm
Width	29mm
Thickness	36mm



## CAS2-00-010-X-W-24V

Optical Information									
Part Number		CAS2-00-010-X-W-24V							
LED Color		WHITE							
Wavelength	(nm)	*Refer to the Chromaticity Table below							
Intensity	(Lux)	8390		4500		3120			
Working Distance	(mm)	10		20		30			
Illumination (number of row)		X							
Illumination Active Area									
Active Area	(mm)	18 X 18							
Emission angle	(deg.)	0							
Eye Safety Class		II							
*CHROMATICITY TABLE									
X	0.296	0.287	0.307	0.311	X	0.311	0.307	0.33	0.33
Y	0.276	0.295	0.315	0.294	Y	0.294	0.315	0.339	0.318
Electrical Information									
Lighting Supply Voltage (constant voltage mode)		24V ± 2%							
Continuous Current	(mA)	130							
Power Consumption	(W)	3.12							
LED temperature, Operating after 60 minutes	°C	60.5							
Lighting casing temperature, Operating after 60 minutes	°C	54.2							
Strobe Mode Specification									
Pulse Operation		YES							
Max. Lighting Supply Voltage (Constant voltage power supply)	(V)	Pulsing at 24VDC to48VDC, 0-10% Duty Cycle Recommended at 36VDC							
Pulse Current, (Max. 10msec) (Constant current power supply)	(mA)	390							
Max. Trigger Pulse Duration	(msec)	10							
Duty Cycle		0-10%							
Additional Information									
Additional Cooling Method		Attached to machine part for better heat dissipation							
Life span in continuous mode		20,000 hours (drop to 50% intensity) at 25°C							
Life span in strobe mode		Est. >50,000 hours (drop to 50% intensity) at 25°C							
Intensity Controller Selection		ANG-Series, LC-Series, STB-Series							
CE Conformity		YES							
RoHS Compliance		YES							
Connection									
Connector Type (Default):		JST SMR-03V							
Cable Length out from lighting :	(mm)	500							
Pin Configuration :		Pin		Signal		Cable Color			
		1		LED +		RED			
		2		N.C.		---			
		3		LED -		WHITE			
									
Application									
Optimal Working Distance	(mm)	10 - 30							